



EM 6, EM 8



The new 2" 4SH hose cutting machine for workshops.
Designed to perfection.



EM 6 M

EM 6 P

EM 8 M

EM 8 P

Unique drive motor with double bearings and oversized shafts

Reduce scrap with straight cuts

More cuts between sharpening increases profits

Less contamination in the shop and in the end product will result in more parts out the door and a better environment in the building

Maximizes motor life, giving you the lowest cost of ownership in the market

Cut faster and generate a more saleable product

Quality steel blade

Long lasting German quality steel blades, lowering the cost of ownership

Compact design

Ideal for a mobile service

CE compliant

Brake motor for safety

Security shield



Guide pins ensure straight cuts, which prolongs blade life.



Requiring only two screws, changing the blade is fast and saves time.

Technical data	EM 6 M	EM 8 M	EM 8 P
Production SAE R 13/ SAE R 15	1 1/2"	1 1/4"	1 1/4"
Workshop SAE R 13/ SAE R 15	2"	2"	2"
SAE R 12	2"	2"	2"
Industry	3"	4"	4"
Max. outside (mm)	Ø 85	Ø 120	Ø 120
Noise level (dBA)	90	90	90
Brake motor	yes	yes	yes
Suction connection (mm)	Ø 60	Ø 60	Ø 60
Drive (kW)	4,6	4,6	4,6
Cutting blade (mm)	TM G 350 x 3 x 30	TM G 400 x 4 x 30	TM G 400 x 4 x 30
L x W x H (mm)	745 x 690 x 430	983 x 460 x 875	983 x 760 x 540
Weight (kg)	75	122	140

Asseccory

- 329.1 - Resettable cutting counter (for EM6)- 323.1 (EM8)
- UMS 4 - Hose measuring tool
- 514.1 - Foot for UMS4 (840 mm)
- UHG 14 - Hose guide 2000 mm
- UHG 14 ext.- Extension 1000 mm
- UVC
- USH 4 Package

Accessories and more information can be found on the this catalogue's jacket.