



Service Crimpers



HM 200



As the unrivaled classic in the 1 1/4" field, with its narrow, innovative construction, high level of user friendliness, versatility and long service life, this HM 200 sets the unbeatable standard for quality and cost effectiveness.

Its compact construction allows for ergonomic working. The use of solid master dies allows you to crimp all types of fittings with the greaseless slide bearing technology, which also reduces maintenance costs.



HM 200

Big opening

Openly built for easy crimping even of 90° elbow pieces, without taking out all dies

Compact Design

Finds a place in every workshop

Slide bearing technology

No greasing improves cleanliness of machine and prolongs its lifetime

Maximum productivity with very low maintenance costs

Flaking cannot stick in grease, no risk of prematurely damaging the crimping head

End product can be used in sanitary applications without cleaning

20% more capability for crimping stronger or more difficult couplings versus our competition's equivalent crimpers

Consistently accurate crimp result

ECOLINE Version

High quality for beginners

CE compliant



HM 200 Ecoline



The micrometer allows you to easily set the crimping diameter.



The large opening stroke allows you to crimp all common types of fittings without changing the crimp dies.



The 12V /24V units offer space- and weight-saving deployment options, e.g. for fitting service trucks.



A box with master dies is available in a package

Technical data	HM 200	HM 200 Ecoline	HM 200 DC
Crimp force (ton)	130		
no grease: 20% less friction			
SAE R13 1 piece	1 1/2"		
SAE R12 2 piece	1 1/4"		
SAE R13 2 piece	1"		
SAE R15 2 piece	1"		
Industry	2"		
90° elbow	1 1/2"		
Max. crimp force (mm) with master dies	70		
Opening (mm)	+ 30		
Opening without dies	100 mm		
Speed (mm/sec)	3,5		
Close + Crimp	5,9		
Open			
Drive	3 kW		
Oil	40 l		4 l
L x W x H (mm)	800 x 530 x 630	800 x 530 x 630	420 x 535 x 520
- Aggregat DC			450 x 270 x 230
Weight (kg)	140	140	88
Accessory			
TA(A)			
QDS 239 B + QDS 239 R + TU-QDS F 239 I + TU-QDS F Basic + TU-QDS F Shelf			
PTS System			
TU Table + TU Rack PB239			
LUF / LUS Lampe			
Options			
Control C.2			
Package			
Machine			
+ PB Ø 17, 20, 24, 28, 32, 40, 44, 50			
+ QDS 239 B			
+ QDC 239.5			