



Service Crimpers

S 4



As the unrivaled classic in the 1¼" field, with its narrow, innovative construction, high level of user friendliness, versatility and long service life, the machine sets the unbeatable standard for quality and cost effectiveness.

Its compact construction allows for ergonomic working. The use of solid master dies allows you to crimp all types of fittings with the tried and tested greaseless slide bearing technology, which reduces maintenance costs and increases product quality.



S 4 C.2



S 4 Ecoline




S 4 DC

Big opening
Openly built for easy crimping even of 90° elbow pieces, without taking out all dies
Compact Design
Finds a place in every workshop
Slide bearing technology
No greasing improves cleanliness of machine and prolongs its lifetime
Maximum productivity with very low maintenance costs
Flaking cannot stick in grease, no risk of prematurely damaging the crimping head
End product can be used in sanitary applications without cleaning
20% more capability for crimping stronger or more difficult couplings versus our competition's equivalent crimpers
Consistently accurate crimp result
ECOLINE Version
High quality for beginners
CE compliant



The S3 serie is fitted with the clean slide bearing technology.



The S3 series can be used to crimp short 90° elbow fittings with a long drop. This is impossible for other conventional machines.



With the double pin connection, it is possible to crimp on both sides of S3 series machines.



PTS System is an accessory



This master die box is in a package available

Technical data	S 4	S4 Ecoline	S4 DC
Crimp force (ton)	180		
No grease: 20% less friction			
SAE R12 4SP 1 piece	2"		
SAE R15 4SH 2 piece	1 1/4"		
SAE R12 4SP 2 piece	2"		
Industry	2"		
90° elbow	1 1/2"		
Max. crimp range (mm) with master dies	70		
Opening (mm)	+ 35		
Opening without dies	105 mm		
Speed (mm/sec)	2,7		0,8
Close + Crimp	2,7		0,8
Open	4,7		1,3
Drive	3 kW		1,8 kW
Oil	35 l		4 l
L x W x H (mm)	720 x 600 x 672	592 x 545 x 672	509 x 430 x 485
Weight (kg)	203	160	132
Options			
Control C.2			
Accessory			
TA(A)			
QDS 239 B + QDS 239 R + TU-QDS F 239 I + TU-QDS F Basic +TU-QDS F Shelf			
PTS System			
TU Table + TU Rack PB239			
LUF / LUS Lampe			
Package			
Machine			
+ PB Ø 17, 20, 24, 28, 32, 40, 47, 54, 62			
+ QDS 239 B			
+ QDC 239.5			