

S 6



Due to its narrow and innovative construction, high level of user friendliness and long service life, the S6 sets new standards for quality and cost effectiveness.

Its compact construction allows for ergonomic working. The use of long master dies allows you to crimp 90° elbow fittings up to 1 ¼" with the tried and tested greasless slide bearing technology, which reduces maintenance costs and increases the product quality.



S 6

Big opening

Openly built for easy crimping even of 90° elbow pieces, without taking out all dies

Big crimping tool

Crimping of 3" industry hoses is made possible

Compact Design

Finds a place in every workshop

Slide bearing technology

No greasing improves cleanliness of machine and prolongs its lifetime

Maximum productivity with very low maintenance costs

Flaking cannot stick in grease, no risk of prematurely damaging the crimping head

End product can be used in sanitary applications without cleaning

20% more capability for crimping stronger or more difficult couplings versus our competition's equivalent crimpers

Consistently accurate crimp result

ECOLINE Version

High quality for beginners

CE compliant



S 6 DC



S6 Ecoline C.2



With the double pin connection, it is possible to crimp on both sides of S3 series machines.



The micro-meter makes it possible to adjust the correct crimping dimension.



The S6 series can be used to crimp short 90° elbow fittings with a long drop. This is impossible for other conventional machines.



As an option you can get the new and user friendly Control C.2



The S6 Ecoline with TU Rack 18-PB239

Technical data	S 6	S 6 Ecoline	S 6 Ecoline DC
Crimp force (ton)	200		
No grease: 20% less friction			
SAE R15 4SH 1 piece	2"		
4SH 2 pieces	2"		
SAE R15 2 ppieces	1 1/2"		
Industry	3"		
90° elbow	2"		
Max. crimp range (mm) with master dies	100		
Opening (mm)	+45		
Opening without dies	147 mm		
Speed (mm/sec)		Phase 3	Phase 1 DC
Close	9,7	4,9	3,6 1,3
Crimp	2,2	2,3	1,3 0,6
Open	16	8,2	6,1 2,1
Drive	4 kW		1,8 kW
Oil	55 l	50 l	44 l
L x W x H (mm)	690 x 600 x 1350	700 x 600 x 735	605 x 505 x 558
Weight (kg)	374	248	238
Option			
Control C.2			
Accessory			
TA(A) QDS 239 B + QDS 239 R + QDS 239 S (not: Ecoline version)+ TU-QDS F 239 I + TU-QDS F Basic +TU-QDS F Shelf PTS System TU Table + TU Rack PB239 LUF / LUS Lampe			
Package			
Machine + PB Ø 17, 20, 24, 28, 32, 40, 44, 50, 57, 71 + 266.239L + QDC 239.5 + QDS 239 B			

More Accessories can be found on pages 21f, as well as on the inside of this catalogue's jacket.