

S 8, S 10



Due to its narrow and innovative construction, high level of user friendliness and long service life, the S8 /10 sets new standards for quality and cost effectiveness.

Its compact construction allows for ergonomic working. The use of long master dies allows you to crimp 90° elbow fittings up to 2" with the tried and tested greaseless slide bearing technology, which reduces maintenance costs and increases the product quality.




S 8 + S 10



19 S 8 Ecoline + S 10 Ecoline

Technische Änderungen vorbehalten. / We reserve the right to make technical changes without notice.
Daten abhängig von der Armatur / Data according to the fitting || Mit Grundbacken / with master dies
Optionen sind Maschinenbauteile, die nur ab Werk lieferbar sind und nicht nachrüstbar || Options are machine parts that can only be ordered while buying the machine.

Big opening
Openly built for easy crimping even of 90° elbow pieces, without taking out all dies
Big crimping tool
Crimping of 4" industry hoses is made possible
Compact Design
Finds a place in every workshop
Slide bearing technology
No greasing improves cleanliness of machine and prolongs its lifetime
Maximum productivity with very low maintenance costs
Flaking cannot stick in grease, no risk of prematurely damaging the crimping head
End product can be used in sanitary applications without cleaning
20% more capability for crimping stronger or more difficult couplings versus our competition's equivalent crimpers
Consistently accurate crimp result
ECOLINE Version
High quality for beginners
CE compliant



The S8 /10 series is fitted with the clean slide bearing technology.



The micrometer gives the possibility to adjust the correct crimping dimension.



As an option you can get the new and user friendly Control C.2.



PS Double Footpedal

Technical data	S 8	S 8 Ecoline	S 10	S 10 Ecoline
Crimp force (ton)	220		280	
No grease: 20% less friction				
SAE R15 4SH 1 piece	2"			
4SH 2 pieces	2"			
SAE R15 2 pieces	1½"		2"	
Industry	4"			
90 ° elbow	2"			
Max. crimp range (mm) with master dies	139			
Opening (mm)	+ 45			
Opening without dies	190 mm			
Speed (mm/sec)				Phase 1
Close	6,1	4,8	6,1	4,8
Crimp	1,7	2,3	1,7	2,3
Open	10,3	7,9	10,3	7,9
Drive	4 kW		5,5 kW	4 kW
Oil	55 l	50 l	55 l	50 l
L x W x H (mm)	690 x 600 x 1400	700 x 600 x 845	690 x 600 x 1400	700 x 600 x 845
Weight (kg)	390	372	390	372
Option				
Control C.2				
Accessory				
TA(A) QDS 239 B + QDS 239 R + QDS 239 S (not in Ecoline version)+ TU-QDS F 239 I + TU-QDS F Basic +TU-QDS F Shelf PTS System TU Table + TU Rack PB239 LUF / LUS Lampe PS Double (not Ecoline)				
Package				
Machine + PB Ø 17, 20, 24, 28, 32, 40, 44, 50, 57, 71 + 266.239L + QDS 239 B + QDC 239.5				

More Accessories can be found on pages 21f, as well as on the inside of this catalogue's jacket.

Technische Änderungen vorbehalten. / We reserve the right to make technical changes without notice.
Daten abhängig von der Armatur / Data according to the fitting || Mit Grundbacken / with master dies
Optionen sind Maschinenbauteile, die nur ab Werk lieferbar sind und nicht nachrüstbar || Options are machine parts that can only be ordered while buying the machine.