

Service Crimpers



UA 4



The powerful workshop crimper UA4 with its capability to crimp a wide range of hoses, up to 1 ¹/₄ SAE R15 or 4 SH (even two-piece versions) offers maximum flexibility at a great value.

The open, horizontally slidable compression dies spring open to facilitate crimping of short 90° fittings with long necks. Thanks to the standard-equipped 115 or 230 V single-phase power unit, the UA4 is ready for operation globally.

This UNIFLEX crimper is also equipped with the legendary greaseless slide bearing technology.



Tools can be changed cleanly and rapidly using the divided crimping die set.



The small, compact design makes the UA4 easy to use and work around.



UA 4

Easy to handle

Openly built for easy crimping even of 90° elbow pieces

Horizontally relocatable stamp for more accessibility

Divided dies for quick and easy changes

Powerfull crimping tool

Makes crimping of hydraulic hoses possible with 1¹/₂" 1 piece and 1¹/₄" 2 pieces 4SP

Compact Design

Finds a place in every workshop

Slide bearing technology

No greasing improves cleanliness of machine and prolongs its lifetime Maximum productivity with very low main-

tenance costs Flaking cannot stick in grease, no risk of prema-

turely damaging the crimping head End product can be used in sanitary applications

without cleaning

20% more capability for crimping stronger or more difficult couplings versus our competition's equivalent crimpers

Consistently accurate crimp result

CE compliant









Easy crimping of elbow pieces

More Accessories can be found on pages 21f, as well as on the inside of this catalogue's jacket.

Technische Änderungen vorbehalten. / We reserve the right to make technical changes without notice. Daten abhängig von der Armatur / Data according to the fitting || Mit Grundbacken / with master dies Optionen sind Maschinenbauteile, die nur ab Werk lieferbar sind und nicht nachrüstbar || Options are machine parts that can only be ordered while buying the machine.

7 Technische Änderungen vorbehalten. / We reserve the right to make technical changes without notice. Daten abhängig von der Armatur / Data according to the fitting || Mit Grundbacken / with master dies Optionen sind Maschinenbauteile, die nur ab Werk lieferbar sind und nicht nachrüstbar || Options are machine parts that can only be ordered while buying the machine.

Technical data	UA 4
Crimp force (ton)	135
No grease: 20% less friction	
SAE R12 4SP 1 piece	1 1/4"
SAE R15 4SH 2 pieces	1"
SAE R12 4SP 2 pieces	1 1/4"
Industry	1 1/2"
90 ° elbow	1 1/4"
Max. crimp range (mm) with master dies	57 + 8 (65)
Opening (mm)	+ 15
Opening without dies	73 mm
Drive	0,75 kW
Oil	51
L x W x H (mm)	380 x 390 x 500
Weight tool (kg)	65
Weight power unit (kg)	25
Accessory	
TU Table	
Package	
Machine	
+ PB 17, 19, 22, 25, 28, 32, 38, 44, 58	